

Multiple coats & UHS floor stripper

Description

Powerful heavy duty stripper especially designed to remove multiple coats of UHS burnished floor emulsions and other tough stripping jobs. Its highly solvenated formula effectively removes all kind of floor emulsions and semi permanent sealers from alkali resistant hard floors and can be used on linoleum to remove multiple layer build-up.

Key properties

- Highly solvenated and alkaline
- High emulsifying power upon contact
- Powerful stripper

Benefits

- Fast penetration of built-up finish and sealer layers
- Designed to work first time, reducing restrrips
- Can be used on alkali resistant floors such as PVC, Vinyl tiles, stone, terrazzo etc.
- Perfect to strip down multiple layers of polish from Linoleum

Use instructions

TASKI Jontec ProStrip needs to be diluted.

1. Dose the product into a tank/bucket filled with cold water.
2. Apply the solution.
3. Allow the product to act for 5-10 minutes.
4. Scrub the floor using a single disc machine equipped with a suitable pad, wet vacuum the soiled solution and rinse thoroughly 2 times with clean water.
5. Damp mop the floor to remove residues.
6. Allow to dry completely before applying additional coats.

Dosage*


Alkali-resistant hard floors: Dose 10% (1L/10 L solution)

Increase concentration up to 25% to remove multiple layer build-up.

Linoleum: Dose max. 10% (1L/10L solution).

Proper dosage and temperature save costs and minimize environmental impacts.

**This dosage is according to optimal conditions, recommendations may vary, please consult with your Diversey representative for directions.*



The logo for Diversey, featuring the brand name in white on a blue oval background with a stylized leaf icon to the right.

Diversey™

TASKI® Jontec ProStrip

F1b

Technical data

Appearance:	Clear pale yellow liquid
Odour:	No Odor/Odorless
pH value (neat):	~ 12
pH value (in use):	~ 11.3
Relative density (g/cm ³ ; 20°C):	≈ 1.01

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; sds.diversey.com. Store in original closed containers away from extremes of temperature. Only for professional users / specialists.

Product compatibility

Test material compatibility before use. Use only cold water. Do not use on alkali sensitive floorings, e.g. cork, wood and marble. Linoleum: Do not use a concentration above 10%. Do not use on solvent sensitive floorings, e.g. asphalt. Immediately remove any solution splashes from alkali sensitive surfaces (e.g. wooden baseboards, painted/varnished surfaces) with a wet cloth.

Environmental information

The surfactants used in this product are biodegradable in compliance with the requirement of EU Detergent Regulation, EC 648/2004.

Available pack sizes

TASKI Jontec ProStrip is available in 2x5L.

www.diversey.com

© 2024 Diversey, Inc. All Rights Reserved. 14/02/2024 en (P99760)